



SIMPLY BETTER DRILLING THROUGH INNOVATION

WE KNOW THE DRILL




DOUBLE INSULATION



VARIABLE SPEED



FORWARD&REVERSE



TWO SPEED GEARSHIFT



BUILT-IN COOLING SYSTEM



REVOLVE SCOPE: $\pm 30^\circ$
MOVE SCOPE: $\pm 8\text{MM}$





OUR COMPANY

Yangzhou Kedi Power Tools Co.,LTD.is one leading manufacturers in china,who is specialized in the production of bench-top power tools,such as magnetic drill,Bench Grinders,Polishing Machines,wet . sharpener.etc. the company was founded in 2000,Kedi has achieved great growth in the past ten years.Now the company has more than 100 employees and around 20 technical engineers

OUR ADVANTAGE

our main markets are Europe and Asia,we have experience about the products quality and request to avoid complaints in the future, which loved by all of our clients.Also we can make samples and production according to customers' requirement and accept the processing order.

"Quality First,Services First"is our company quality polity.we will try our best to meet customer requests,provide great services to all of our customers."innovation,integrity,win-win"is our cooperation policy.

Welcome to visit our factory and looking forward to working together with you!



J1C-13S

J1C-16S



Including
Keyless Drill Chuck



Twist Drill not included



Model No.
Rated Voltage
Rated Frequency
Motor Power
No Load Speed
Magnet Adhesion
Twist Drill
Stroke
N.W
Carton Package size

J1C-13S
110/220V
50/60HZ
1050W
590RPM
10000N
Ø 1.5-13mm
150mm
12.5kg
49×41×20cm(Carton)

J1C-16S
110/220V
50/60HZ
1050W
590RPM
10000N
Ø1.5-16mm
150mm
12.5kg
49x41x20cm(carton)

Variable Speed Feature

J1CT-13S:Variable Speed (100-720RPM)
J1CT-16S:Variable Speed (100-720RPM)
Optional:Swivel Base

Variable Speed and Forward&Reverse Feature

J1CD-13S:Variable Speed and Forward&Reverse
J1CD-16S:Variable Speed and Forward&Reverse
Optional:Swivel Base

J1C-23S

J1C-28S



NOT INCLUDED



Model No.	J1C-23S	J1C-28S
Rated Voltage	110/220V	110/220V
Rated Frequency	50/60HZ	50/60HZ
Motor Power	1200W	1200W
No Load Speed	500RPM	500RPM
Magnet Adhesion	13900N	13900N
Twist Drill	Ø 2.5-23mm	Ø2.5-28mm
Stroke	160mm	160mm
Spindle Taper	MT2	MT3
N.W	20kg	21kg
Carton Package size	50×47×20cm(Carton)	50×47×20cm(Carton)

Variable Speed Feature

J1CT-23S:Variable Speed (100-650RPM)
 J1CT-28S:Variable Speed (100-650RPM)
 Optional:Swivel Base

Variable Speed and Forward&Reverse Feature

J1CD-23S:Variable Speed and Forward&Reverse
 J1CD-28S:Variable Speed and Forward&Reverse
 Optional:Swivel Base


J3C-32S
J3C-38S
J3C-49S



Model No.	J3C-32S	J3C-38S	J3C-49S
Rated Voltage	380V	380V	380V
Rated Frequency	50HZ	50HZ	50HZ
Motor Power	1200W	1400W	1500W
No Load Speed	170RPM	150RPM	120RPM
Magnet Adhesion	20000N	20000N	20000N
Twist Drill	Ø 2.5-32mm	Ø 2.5-38mm	Ø 2.5-49mm
Stroke	220mm	220mm	220mm
Spindle Taper	MT4	MT4	MT4
N.W	42kg	42KG	42kg
Package size	55×50×24cm	55×50×24cm	55×50×24cm
(Plywood Carton)			
Optional:Swivel Base			

J1CD-32S

J1C-35W



Model No.

Rated Voltage
Rated Frequency
Motor Power
No Load Speed
Magnet Adhesion
Twist Drill
Max Drilling
Max Depth
Stroke
Spindle Taper
N.W
Carton Package size

J1CD-32S

110/220V
50/60HZ
1400W
100-500RPM
20000N
Ø 2.5-32mm
/
/
220mm
MT4
30kg
53×44×20cm(Carton)

J1C-35W

110/220V
50/60HZ
1260W
550RPM
12800N
/
35mm
50mm
50mm
MT3
9kg
30×25×18cm

Variable Speed and Forward&Reverse

Optional:Swivel Base

J1C-35S

J1C-60S



Model No.

Rated Voltage

Rated Frequency

Motor Power

No Load Speed

Magnet Adhesion

Twist Drill

Core Drill

Max Depth

Stroke

Spindle Taper

N.W

Package size

J1C-35S

110/220V

50/60HZ

1050W

550RPM

10000N

1.5-13mm

12-35mm

50mm

150mm

Weldon 19mm

12.5kg

49×41×20cm(Carton)

J1C-60S

110/220V

50/60HZ

1200W

460RPM

13900N

1.5-13mm

12-60mm

50mm

150mm

Weldon 19mm

22kg

50×47×20cm(Carton)

Variable Speed Feature

J1CT-35S:Variable Speed (150-720RPM)

J1CD-35S:Variable Speed and Forward&Reverse

Optional:Swivel Base

Variable Speed and Forward&Reverse Feature

J1CT-60S:Variable Speed (120-650RPM)

J1CD-60S:Variable Speed and Forward&Reverse

Optional:Swivel Base

J3C-23S

J3C-28S



NOT INCLUDED

Model No.

Rated Voltage

Rated Frequency

Motor Power

No Load Speed

Magnet Adhesion

Twist Drill

Stroke

Spindle Taper

N.W

Carton Package size

Optional:Swivel Base

J1C-23S

380V

50HZ

1100W

330RPM

13900N

Ø 2.5-23mm

160mm

MT2

21kg

50×47×20cm(Carton)

Optional:Swivel Base

J3C-28S

380V

50HZ

1100W

300RPM

13900N

Ø2.5-28mm

160mm

MT3

21kg

50×47×20cm(Carton)

J1C-35H



Model No.	J1C-35H
Rated Frequency	50/60HZ
Motor Power	1050W
No Load Speed	600RPM
Magnet Adhesion	9000N
Twist Drill	Ø 1.5-13mm
Core Drill	Ø12-35mm
Max Depth	50mm
Stroke	150mm
Spindle Taper	Weldon 19mm
N.W	14kg
Package size	49×41×20cm(Carton)

Optional:Swivel Base

J1C-60H

Model No.	J1C-60H
Rated Voltage	110/220V
Rated Frequency	50/60HZ
Motor Power	1200W
No Load Speed	550RPM
Magnet Adhesion	13600N
Twist Drill	Ø1.5-13mm
Core Drill	Ø12-60mm
Max Depth	50mm
Stroke	160mm
Spindle Taper	Weldon 19mm
N.W	22kg
Package size	50×47×20cm(Carton)

Optional:Swivel Base



J1CD-45D

J1CD-60D



Model No.

Rated Voltage

Rated Frequency

Motor Power

No Load Speed

Magnet Adhesion

Twist Drill

Core Drill

Max Depth

Max Tapping

Stroke

Spindle Taper

N.W

Package size

Optional

J1CD-45D

110/220V

50/60HZ

1200W

260-550RPM

10000N

Ø1.5-13mm

Ø12-45mm

50mm

M12

200mm

Weldon 19mm

N.15KG

47x44x20(carton)

Swivel Base

J1CD-60D

110/220V

50/60HZ

1800W

60-520RPM

13900N

Ø 2.5-32mm

Ø 12-60mm

50mm

M27

200mm

MT3




22Kg

53x44x20cm

Swivel Base

J1CD-100D

J1C-150



Model No.

Rated Voltage

Rated Frequency

Motor Power

No Load Speed

Magnet Adhesion

Twist Drill

Core Drill

Max Depth

Max Tapping

Stroke

Spindle Taper

N.W

Package size

Optional

J1CD-100D

110/220V

50/60HZ

2000W

50-520RPM

20000N

2.5-50mm

12-100mm

50mm

M38

210mm

MT4

31KG

76x44x22(carton)

Swivel Base

J1C-150

110/220V

50/60HZ

1500W

150- 550RPM

/

/

15-150mm

/

M27

220mm

Weldon19mm

15Kg

73.5x44x22cm

Swivel Base

ACCESSORIES




1.5-13mm 3-16mm 5-22mm

Keyless Drill Chuck



TCT/HSS Annular Cutter



MT2 MT3 MT4

Morse Taper Drill Chuck Arbor



MT2 MT3 MT4

Morse Taper Drill Sleeve



Drill chuck Adapter



Arbor with coolant feed

WET STONE SHARPENER

Wet and dry grinder NTS250 and NTS250Pro

The wet and dry grinding machine can easily and quickly achieve perfect grinding results. Universally to grind metal (axes,gouges,knives, planer blades,scissors) glass,stones and other materials.



NTS250



NTS250PRO WITH DIGITAL DISPLAY

Grinding wheel Size:250 x 50 x 12 mm
Stropping wheel Size:200 x 30 x 12 mm
Grinding Wheel Material :Aluminum Oxide
Stropping wheel material:ABS/Leather
Motor speed:1450 min-1
Grinding Speed :90 rpm /80-160
Motor power input :200 W
Voltage :230 V
Dimensions:340x280x460mm
Weight approx.:19.5kg
Packaging:Carton Box with styrofoam
Packaging size:36.5x31.5x43cm

Features:

Universal Tool Support 12mm
Water Reservoir
Included 220 Grit Aluminum Oxide Grinding Wheel
Included Leather Stropping Wheel
Included Angle Guide
Includes Straight Edge Jig