

Mobil ATF 320

Automatic Transmission Fluid

Product Description

Mobil ATF 320 is an extra high performance automatic transmission fluid exceeding the latest revised specifications of Ford Mercon and General Motors, Dexron III Specifications.

Mobil ATF 320 is recommended for most passenger car and commercial automatic transmissions. It is also suitable for power steering systems, hydraulic applications and some manual transmissions where an automatic transmission fluid is specified.

Features and Benefits

- The correct frictional requirements to give smooth transmission operation over wide operational bands
- Protection against degradation at high operating temperature and extended service
- Low temperature pumpability and circulation ensuring cold start performance
- Compatibility with all conventional seal materials found in transmission units

Applications

Mobil ATF 320 is recommended for most passenger car and commercial automatic transmissions. It is also suitable for power steering systems, hydraulic applications and some manual transmissions where an automatic transmission fluid is specified.

It is particularly designed for automatic transmissions requiring a Ford Mercon or GM type fluid approved against Dexron III specification.

Specifications and Approvals

Mobil ATF 320 has the following builder approvals:

Ford Mercon M931220	X
Allison C4 (31574001)	X
Voith G607	X
ZF TE-ML 4D, 17 C	X

Mobil ATF 320 is recommended for use in applications requiring:

GM Dexron III	X
Renk Doromat	X



Typical Properties

Mobil ATF 320

SAE Grade

Viscosity, ASTM D 445

cSt @ 100°C

8.2

Brookfield viscosity @ -40°C, mPa.s, ASTM D2983

17900

Flash Point, °C, ASTM D92

197

Density @ 15 °C kg/l, ASTM D 4052

0.863

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobil ATF 320 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.