











Our engineers know that the market needs a lighting tower that is rugged, long lasting and safe. The X-HYBRID MOBILE has been created beginning from these characteristics. It is the best solution to your needs and guarantees 3000 sqm of illuminated area. 7 units can be loaded on a standard truck. To all of this, we added the technology that allows for maximum fuel efficiency and reliability.













8,5m 1280 Kg 340

3000 sqm 220(l) - 0,55(l/h) battery

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5m, 340° rotatable
- Standard light sensor for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 7 units per truck
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine proteciton and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Fully bunded tank, 110%
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization







Special events



Rural & hard to reach areas



Emergency response



Construction & work sites



Gas, oil & mining operations



Military applications












(Units Per Truck



You can place 7 units on a single vehicle thanks to one of the compactest footprints on the market.



technical data


Dimensions & weight	
Dimensions min. (mm)	2944 x 1466 x 2570
Dimensions max. (mm)	2944 x 2928 x 8500
Total weight without fuel	1280 Kg
Features	
Rotation	340°
Floodlights	4x150W
IP Level	67
Options	Timer
Alternator	
Model	Linz Alumen SB
Rated output Kva	3.5
Frequency Hz	50
Voltage V	230
Insulation class	Н
Degree of Protection	IP23
Standard load dolivory	

Engine	
Model	Kubota Z482
Fuel	Diesel
rpm	1500
Tank capacity (I)	222
Fuel consumption (I/h)	0,55
Running time (h)	1.180
Noise level at 7mt	62
Batteries	
Туре	AGM ZL 06 130
Batteries number	4
Batteries pack	24V DC 400 Ah
Expected battery cycle	500
Expected battery life time (h)	13000
Hybrid mode	
Running time (h)	18
Charging time with LED's ON (h)	
Charging time with LED's OFF (h)	
Complete discharge / charge cycle (h) 26	

0,17

Standard load delivery

7 sets




Units Per Truck

Illuminated area

3000 sqm

Hybrid mode consumption (I/h)





Эксклюзивный официальный дистрибьютор TRIME на территории России и СНГ

+7 (495) 532-37-34 | +7 (925) 741-89-01 8 (800) 222-51-05 (Бесплатно для всех регионов)

www.legion-tehno.ru | trime@legion-tehno.ru

Компания TRIME оставляет за собой право изменять технические характеристики и товары, описанные в этом каталоге, в любое время и без предварительного уведомления по техническим или коммерческим причинам. Изображения продуктов показаны только для информации.