











# X-HYBRID

6x150W - LED - 9M

Our engineers know that the market needs a lighting tower that is rugged, long lasting and safe. The X-HIBRID has been created beginning from these characteristics. It is the best solution to your needs and guarantees 3800 sqm of illuminated area. 20 units can be loaded on a standard truck. To all of this, we added the technology that allows for maximum fuel efficiency and reliability.













8,5m 1150Kg 340°

3800 sqm 150(l) - 0,55(l/h) battery

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5m, 340° rotatable
- Standard light sensor for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 20 units per truck
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Fully bunded tank, 110%
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization



### **APPLICATIONS**



Special events



Rural & hard to reach areas



Emergency response



Construction & work sites



Gas, oil & mining operations




Military applications












20 Units Per Truck



You can place 20 units on a single vehicle thanks to one of the compactest footprints on the market.



#### technical data

Dimensions & weight	
Dimensions min. (mm)	1200 x 1200 x 2560
Dimensions max. (mm)	2520 x 2520 x 8500
Total weight without fuel	1150 Kg
Features	
Rotation	340°
Floodlights	6x150W
IP Level	67
Options	Timer
Alternator	
Model	Linz Alumen SB
Rated output Kva	3.5
Frequency Hz	50
Voltage V	230
Insulation class	Н
Degree of Protection	IP23
Standard load delivery	

Engine	
Model	Kubota Z482
Fuel	Diesel
rpm	1500
Tank capacity (I)	150
Fuel consumption (I/h)	0,55
Running time (h)	608
Noise level at 7mt	62
Batteries	
Туре	AGM ZL 06 130
Batteries number	4
Batteries pack	24V DC 400 Ah
Expected battery cycle	500
Expected battery life time (h)	9500
Hybrid mode	
Running time (h)	11
Charging time with LED's ON (h)	11

8

19


0.23

Charging time with LED's OFF (h)

Complete discharge / charge cycle (h) Hybrid mode consumption (l/h)

Standard load delivery


#### 20 sets



Units Per Truck

Illuminated area

### 3800 sqm





## Эксклюзивный официальный дистрибьютор TRIME на территории России и СНГ

+7 (495) 532-37-34 | +7 (925) 741-89-01 8 (800) 222-51-05 (Бесплатно для всех регионов)

www.legion-tehno.ru | trime@legion-tehno.ru

Компания TRIME оставляет за собой право изменять технические характеристики и товары, описанные в этом каталоге, в любое время и без предварительного уведомления по техническим или коммерческим причинам. Изображения продуктов показаны только для информации.