

Overcurrent Protection SIPROTEC 7SJ600

Protection
SIPROTEC 4

Product description	Variants	Order No.
Numerical overcurrent-time protection relay SIPROTEC 7SJ600 Overload protection, fault recording unbalanced-load protection, binary input voltage: 24 to 250 V with isolated RS485 interface	<u>Current transformer</u> 1 A ¹⁾ , 50/60 Hz 5 A ¹⁾ , 50/60 Hz <u>Auxiliary voltage</u> DC 24 V, DC 48 V DC 60 V, DC 110 V, DC 125 V ²⁾ DC 220 V, DC 250 V; AC 115 V ²⁾ AC 230 V ³⁾ <u>In 7XP20 housing</u> for surface mounting, side terminal connection Terminal connection on top and bottom ³⁾ for flush mounting/cubicle mounting <u>Language</u> English, German, Spanish, French, Russian Without autoreclosure With autoreclosure Without control With control Without UL Listing With UL Listing	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 7 S J 6 0 0 □ - □ □ A □ 0 - □ D □ □ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ ↑ 1 5 2 4 5 6 B D E 0 0 1 A B 0 1

1) Rated current 1/ 5 A can be selected by means of jumpers.
 2) Transition between the two auxiliary voltage ranges can be selected by means of jumpers
 3) Only when position 16 is not "1" (with UL Listing)