

Gas,oil &mining operations

Special events

Emergency

Military applications





Operation: ENGINE POWERED fuel tank capacity 220 litres Kubota Z482



ENGINE POWERED Line













FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- Standard light sensor for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 22 units per truck
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine proteciton and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Fully bunded tank, 110%
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization













Dimensions & weight	Dimensions min (mm)				Dimensions max(mm)				Total weight (kg)				
	1200x1200x2560 (LxWxH)				2390x2390x8500 (LxWxH)				1013				
Floodlights	Туре	Po	Power (each)		Floodlights r	number	ber Options		Illuminated		area (sqm)		
	Led	16	160W		6		Timer	Timer			4200		
Mast	Lifting method I		Max Height		Max Wind Speed		Rotation	Rotation					
	Hydraulic		8,5 m		110 km/h		340°	340°					
Alternator	Model	Fre	Frequency (Hz)		Insulation class		Degree of protection		Single phase voltage		Auxiliary outlets		
	Synchronous	50	50		Н		IP 23		3,5kVA - 230V		1,2 kVA		
Engine	Model	Fuel	Fuel r.p.m.		Tank capacity (I)	C	Consumption (I/I		h) Running time		Noise level (dBA) at 7m		
	Kubota Z482	Diesel	1500		220	0	0,55		400 h		65		



Эксклюзивный официальный дистрибьютор TRIME на территории России и СНГ

trime.ru info@trime.ru

+7 (929) 653-13-37 | +7 (495) 741-89-01 8 (800) 222-51-05 | +7 (495) 532-37-34