

TRIME.RU

CLT. 10

TRIME

TRIME

Gas,oil &minin operations

TRINE

24.500 SQM Area illuminated



15°

Automatic levelling of the undercarriage



Operation: **ENGINE POWERED** fuel tank capacity 150 litres **Kubota D1105**



15°

INE ONSTER **30X150W LED HEADS**



INTEGRATED DRIVE SYSTEM (remote controller)



| Very Robust | RU Č | IME tank | | | | | | | | | | | | | | |
|---|------------------------|------------------|----------|----------------|--------------------------|-----------------------|----------------------|------------------------|-------|-----------------------------------|------------|------------------------------|---------------------------|-------------------------|----------------------------|--|
| NOISE Juice Noise | 24. area | 24.500 sqm | | | | | 3 units per truck | | | | | ideal f ihe mi 50 5 | or ne | | | |
| Dimensions & weight | Dimensions (mm) | | | | | TOT tower height (mm) | | | | n m) | T | Total weight (kg) | | | | |
| | 3300x1490x1980 (LxWxH) | | | | | | 1000 | | | | 3 | 000 | | | | |
| Floodlights | Туре | ype Power (each) | | |) Floodlights n | | | Illuminated area (sqm) | | | Options | | |) TOT power | | |
| | Led | Led 150W | | | | | | 24.500 | | | opuolis | | 5700W (4x1200W + 1x1900W) | | | |
| Mast | Lifting I | | Max Heig | | | | Max Wind Sp | Max Wind Speed | | | Rotation | | | | | |
| | Hydrauli | | 8, | 5 m | | | | 110 km/h | | 340° | | | | | | |
| Alternator | Model | | | Frequency (Hz) | | | sulation class | | | Degree of protection | | DC Voltage | | Outlet auxiliary socket | | |
| | Synchronous | | Į | 50 | | Н | | | IP 23 | | 48V | | | yes | | |
| Engine | Model Fu | | Fuel | el r.p | | | Tank capacity (I) | |) | Consumption | (l/h) Runr | | unning time | | Noise level (dBA) at 7m | |
| | Kubota D1105 Die | | | sel 1500 | | | 150 | | | 1,6 | | 94 h | 94 h | | 65 | |
| General | Power generator | | | | Maximum driving speed | | | dynami Iling |) | Consolle-frontal panel control | | | Longitudina levelling | | Longitudinal levelling | |
| | 9 KVA | | | 12,2 | 12,2 km/h | | | | | by cable | | +/- | +/- 15° | | +/- 15° | |



Эксклюзивный официальный дистрибьютор **TRIME** на территории России и СНГ

trime.ru | info@trime.ru +7 (929) 653-13-37 | +7 (495) 741-89-01 8 (800) 222-51-05 | +7 (495) 532-37-34

FEATURES

- Multi-directionally electric adjustable and tiltable LED panel
- 10 meters hydraulic and foldable mast
- Galvanized metalworks
- 80 µc powder coating
- Robust lifting eyes
- Cable protected inside the mast with automatic reel
- Circuit breaker for electrical protection
- · Outlet auxiliary socket
- High efficiency Kubota engine coupled with heavy duty Linz Electric alternator
- Wide crawler undercarriage to be secure and stable in any situation
- · Constantly horizontal thanks to the dynamic levelling technology

- DSE 401
- Electric light Tilting



 $^{\circ}$

Fuel tank

150L-1,6L/h