









FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- · Central lifting eye
- Certified wind stability up tp 80 km/h
- 4 height adjustable stabilizers + front jockey wheel
- On board levels for guidance during stabilization
- No. 8 batteries AGM, Battery Pack 24Vdc 800Ah
- EU Homologated Road-tow trailer
- VICTRON controller for Tracking and Telematics e remote management





















Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)			Total weight (kg)	
	3360x2138x2522 (LxWxH)		3360x4150x8500 (LxWxH)			1500	
Floodlights	Туре	Power (each)		Floodlights number	IP level		Illuminated area (sqm)
	Led	60W		4	65		2400
Mast	Lifting method	Max Height		Max Wind Speed	Rotation		
	Hydraulic	8,5 m		80 km/h	340°		
Batteries	Туре	Batteries number		Power Battery pack	Expe	Expected battery cycle	
	AGM sealed-maintenace free	8		24 Vdc 800 ah	500		
Solar panel	Power (each)	Туре		Solar panel deployment		Solar charge control	
	360 W	4xVictron		manual		MPPT 150/60	

Running Time with Solar charge

All year round



Эксклюзивный официальный дистрибьютор TRIME на территории России и СНГ

trime.ru info@trime.ru

+7 (929) 653-13-37 | +7 (495) 741-89-01 8 (800) 222-51-05 | +7 (495) 532-37-34