

Gas,oil &mining operations

Military applications

WA



ENGINE POWERED Line



Operation: **ENGINE POWERED** fuel tank capacity 115 litres Kubota D1105



X-RENT6x320W 48V LED - 8,5M











FEATURES

- 6x320W high efficiency LED floodlight system
- Illuminated area 5400 sgm
- On/Off switches one every two lamps
- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower
- Max height 8,5m
- Hydraulic lifting system
- 340°ruotable mast
- Fully bunded tank, 110%
- Control panel alarms for engine protection and fuel level indicator
- Simple, rugged machine design and layout
- Guided main coiled cable to avoid damage during tower operation
- On board level for guidance during stabilization
- Galvanized metalwork, 80 µm powder coating
- Wind stability up to 80 km/h
- Eye tow hitch-43mm
- . Low speed tow trailer single chassis with lights
- 4 height adjustable stabilizers, manual deployment, galvanized steel, leveling system
- Central lifting eye & side forklift pockets
- Very compact dimensions for easy handling











Dimensions & weight	Dimensions min (mm)				Dimensions max(mm)				Total weight (kg)			
	2560x1380x2500 (LxWxH)				2560x2170x8500 (LxWxH)				1100			
Floodlights	Туре		Power (each)		Floodlights number		Options		Illuminated area (sqm)			
	Led		320W		6		Homologa	Homologated axle & towing hitc		5400		
Mast	Lifting method Ma		Max Height		Max Wind Speed		Rotation	Rotation				
	Hydraulic		8,5 m		110 km/h		340°	340°				
Alternator	Model	Fre	Frequency (Hz)		ulation class	Degree of protection		Single phase voltage		ge	Auxiliary outlets	
	Synchronous		50 H		-l IP		23		8,5 kWA		1x16A - 240V	
Engine	Model	Fuel	l r.p.m.		Tank capacity (I	Ca	Consumption (I/h)		Running time		Noise level (dBA) at 7m	
	Kubota D1105	Diesel	el 1500		115		1,6		71 h		68	



Эксклюзивный официальный дистрибьютор TRIME на территории России и СНГ

trime.ru | info@trime.ru

+7 (929) 653-13-37 | +7 (495) 741-89-01 8 (800) 222-51-05 | +7 (495) 532-37-34