





PLUG-IN Line



T-ZEROPRO





FEATURES

max height

7 m

kq

Kg 330

rotation

4

POWER

340°

- ATEX lighting tower for explosive areas
- Multi-directionally adjustable and tiltable floodlights
- 5 sections hydraulic vertical tower 7m, 340° rotatable
- Manual lifting systm by winch complete with auto-braking system
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 32 units per truck
- Light weight for improved manoeuvrability
- Central lifting eye, forklift pockets for effective handling
- Armored cable c/w plug to light up the unit
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization
- Patented mast emergency brake which prevents the falling of the mast in case of cable fallure



The first lighting tower in the market that has a patented mast emergency brake system to improve safety of the operators on site Registration number: 102017000044431

ZERO emissions	ZERO fuel costs	ZE nois	ERO S		MINIMAL sevice				
LINKABLE TOWERS	2400 sqm area illuminated		SY J	& transportability	units pe			Complete SILENCE on work time 8 HOURS A DAY 7 DAYS A WEEK	
Dimensions & weight	Dimensions min (mm)			Dimensions max(mm)			Total weight (kg)		
	1200x850x2100 (LxWxH)			1850x1450x7000 (LxWxH)			330		
Floodlights ATEX	Туре	Power (each)		Floodlights number	IP level		Illuminate	d area (sqm)	
	Led	88W		4	65		2400		
Mast	Lifting method	Max Height		Max Wind Speed	Rotation	Pa	atented mast er	nergency system	
	Manual	7 m		110 km/h	340°	y	es		
Input&output	Inlet plug	General		Tower lifting metod		Trailer type			
				Manual					



Эксклюзивный официальный дистрибьютор TRIME на территории России и СНГ

trime.ru info@trime.ru

+7 (929) 653-13-37 | +7 (495) 741-89-01 8 (800) 222-51-05 | +7 (495) 532-37-34