

4

3

2

1

B

B

4X M6 THRD HOLES
(PER HALF) EQU SPC

SLOTTED BRACKET

Ø3.00

BRACKET

15.00°

50.00°

HOLE LOCATION PLUS BRACKETS

1/4 NPT
INLET

Ø1.00

5.80

9.18

Ø3.75

1.01

A

A

4

3

2

1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
NEXFLOW. ANY REPRODUCTION IN PART
OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF NEXFLOW IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED		NAME	DATE	NEX FLOW™ AIR PRODUCTS CORP. 10520 YOUNG STREET, UNIT 35B220, RICHMOND HILL, ON, L4C 3C7 TEL: (416) 410-1313 & FAX: (416) 410-1806 www.nexflow.com	
		DIMENSIONS ARE IN INCHES		DRAWN	AMMAD	APR/23/21	TITLE:
		TOLERANCES:		CHECKED			1" RING BLADE
		FRACTIONAL ±		ENG APPR.			SIZE MODEL #:
		ANGULAR: MACH ± BEND ±		MFG APPR.			B 20001
		TWO PLACE DECIMAL ±		Q.A.			REV
		THREE PLACE DECIMAL ±					1
		INTERPRET GEOMETRIC TOLERANCING PER:				SCALE: 1:1.5 WEIGHT:	
		MATERIAL				SHEET 1 OF 1	
		FINISH					
NEXT ASSY	USED ON	APPLICATION		DO NOT SCALE DRAWING			